

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No.: 10/684,441

**AMENDMENTS TO THE CLAIMS**

**This listing of claims will replace all prior versions and listings of claims in the application:**

**LISTING OF CLAIMS:**

1. (Original) A step-up apparatus comprising:

a first level shift circuit for receiving a first clock signal to generate two phase-opposite second clock signals;

a second level shift circuit for receiving said first clock signal to generate two phase-opposite third clock signals;

a charge pump circuit, connected to said first level shift circuit, for stepping up a power supply voltage at a power supply voltage terminal using said second clock signals to generate a positive voltage; and

a polarity inverting circuit, connected to said charge pump circuit and said second level shift circuit, for inverting said positive voltage using said third clock signals to generate a negative voltage whose absolute value is the same as said positive voltage,

a high level of said second clock signals being not higher than said positive voltage,

a low level of said second clock signals being not lower than a voltage at a ground terminal,

a high level of said third clock signals being not higher than said power supply voltage,

a low level of said third clock signals being not lower than said negative voltage.

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No.: 10/684,441

2. (Original) The step-up apparatus as set forth in claim 1, wherein said first level shift circuit comprises:

first and second cross-coupled load P-channel MOS transistors whose sources receive said positive voltage; and

first and second N-channel drive MOS transistors whose drains are connected to drains of said first and second cross-coupled load P-channel MOS transistors, respectively,

gates of said first and second N-channel drive MOS transistors receiving said first clock signal and its inverted signal, respectively,

the drains of said first and second N-channel drive MOS transistors generating said second clock signals.

3. (Original) The step-up apparatus as set forth in claim 1, wherein said second level shift circuit comprises:

first and second cross-coupled N-channel Load MOS transistors whose sources receive said voltage at said ground terminal; and

third and second P-channel drive MOS transistors whose sources receive said power supply voltage and whose drains are connected to drains of said first and second cross-coupled load N-channel MOS transistors, respectively,

gates of said first and second drive P-channel MOS transistors receiving said first clock signal and its inverted signal, respectively,

the drains of said first and second P-channel drive MOS transistors generating said third clock signals.

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No.: 10/684,441

4. (Currently Amended) The step-up apparatus as set forth in claim 1, wherein said ~~change~~ charge pump circuit comprises:

a first circuit including a first step-up switching element, connected to said power supply voltage terminal, for generating said power supply voltage; and

an i-th ( $i=2, 3, \dots, K$ ) circuit including a charging capacitor, a first charging ~~switching~~ element connected between said ground terminal and said charging capacitor, a second charging element connected between said charging capacitor and said power supply voltage terminal, and a second step-up switching element connected to said charging capacitor and said second charging ~~switching~~ element for generating an “i” times said power supply voltage.

5. (Currently Amended) The step-up apparatus as set forth in claim 4, wherein each of said first and second step-up switching elements comprises a P-channel MOS transistor controlled by one of said second clock signals,

said first charging ~~switching~~ element ~~comprising~~ comprises an N-channel MOS transistor controlled by the one of said second clock signals, and

said second charging ~~switching~~ element ~~comprising~~ comprises a P-channel MOS transistor controlled by the other of said second clock signals.

6. (Currently Amended) The step-up apparatus as set forth in claim 1, wherein said charge pump circuit steps up said power supply voltage further using said third clock signals, said pump circuit comprising:

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No.: 10/684,441

a first circuit including a first step-up switching element, connected to said power supply voltage terminal, for generating said power supply voltage; and

an i-th ( $i=2, 3, \dots, K$ ) circuit including a charging capacitor, a first charging ~~switching~~ element connected between said ground terminal and said charging capacitor, a second charging element connected between said charging capacitor and said power supply voltage terminal, and a second step-up switching element connected to said charging capacitor and said second charging ~~switching~~ element for generating an "i" times said power supply voltage,

said first step-up switching element comprising a P-channel MOS transistor controlled by one of said third clock signals,

said second charging ~~switching~~ element of said 2-nd circuit comprising a P-channel MOS transistor controlled by the other of said third clock signals,

said first charging ~~switching~~ element of said i-th ( $i=2, 3, \dots$ ) circuit comprising an N-channel MOS transistor controlled by the one of said second clock signals,

said second charging ~~switching~~ element of said i-th ( $i=3, 4, \dots$ ) circuit comprising a P-channel MOS transistor controlled by the other of said second clock signals,

said second step-up switching element comprising a P-channel MOS transistor controlled by the other of said second clock signal.

7. (Original) A step-up apparatus comprising:

a first level shift circuit for receiving a clock first signal to generate two phase-opposite second clock signals;

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No.: 10/684,441

a second level shift circuit for receiving said first clock signal to generate a third clock signal;

a charge pump circuit, connected to said first level shift circuit, for stepping up a power supply voltage at a power supply voltage terminal using said second clock signals to generate a positive voltage; and

a polarity inverting circuit, connected to said charge pump circuit and said second level shift circuit, for inverting said positive voltage using said third clock signal to generate a negative voltage whose absolute value is the same as said positive voltage,

a high level of said second clock signals being not higher than said positive voltage,

a low level of said second clock signals being not lower than a voltage at a ground terminal,

a high level of said third clock signal being not higher than said voltage at said ground voltage,

a low level of said third clock signal being not lower than said negative voltage.

8. (Original) The step-up apparatus as set forth in claim 7, wherein said first level shift circuit comprises:

first and second cross-coupled load P-channel MOS transistors whose sources receive said positive voltage; and

first and second N-channel drive MOS transistors whose drains are connected to drains of said first and second cross-coupled load P-channel MOS transistors, respectively,

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No.: 10/684,441

gates of said first and second N-channel drive MOS transistors receiving said first clock signal and its inverted signal, respectively,

the drains of said first and second N-channel drive MOS transistors generating said second clock signals.

9. (Original) The step-up apparatus as set forth in claim 7, wherein said second level shift circuit comprises:

a polarity inverting circuit for inverting said first clock signal;

first and second cross-coupled N-channel Load MOS transistors whose sources receive said negative voltage; and

third and second P-channel drive MOS transistors whose sources receive said voltage at said ground terminal and whose drains are connected to drains of said first and second cross-coupled load N-channel MOS transistors, respectively,

gates of said first and second drive P-channel MOS transistors receiving an output signal of said polarity inverting circuit and its inverted signal, respectively,

the drain of one of said first and second P-channel drive MOS transistors generating said third clock signal.

10. (Original) The step-up apparatus as set forth in claim 9, wherein said polarity inverting circuit comprises a capacitor for receiving said first clock signal and a diode between said capacitor and said ground terminal.

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No.: 10/684,441

11. (Currently Amended) The step-up apparatus as set forth in claim 7, wherein said ~~change~~ charge pump circuit comprises:

a first circuit including a first step-up switching element, connected to said power supply voltage terminal, for generating said power supply voltage; and

an i-th ( $i=2, 3, \dots, K$ ) circuit including a charging capacitor, a first charging ~~switching~~ element connected between said ground terminal and said charging capacitor, a second charging element connected between said charging capacitor and said power supply voltage terminal, and a second step-up switching element connected to said charging capacitor and said second charging ~~switching~~ element for generating an “i” times said power supply voltage.

12. (Currently Amended) The step-up apparatus as set forth in claim 11, wherein each of said first and second step-up switching elements comprises a P-channel MOS transistor controlled by one of said second clock signals,

said first charging ~~switching~~ element comprising an N-channel MOS transistor controlled by the one of said second clock signals,

said second charging ~~switching~~ element comprising a P-channel MOS transistor controlled by the other of said second clock signals.

13. (Original) A step-up apparatus comprising:

a first level shift circuit for receiving a clock first signal to generate two phase-opposite second clock signals;

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No.: 10/684,441

a second level shift circuit for receiving said first clock signal to generate two phase-opposite third clock signals;

a charge pump circuit, connected to said first level shift circuit, for stepping up a power supply voltage at a power supply voltage terminal using said second clock signals to generate first and second positive voltages, said first positive voltage being smaller than said second positive voltage; and

a polarity inverting circuit, connected to said charge pump circuit and said second level shift circuit, for inverting said second positive voltage using said third clock signals to generate a negative voltage whose absolute value is the same as said second positive voltage,

a high level of said second clock signals being not higher than said second positive voltage,

a low level of said second clock signals being not lower than a voltage at a ground terminal,

a high level of said third clock signals being not higher than said power supply voltage,

a low level of said third clock signals being not lower than said negative voltage.

14. (Original) The step-up apparatus as set forth in claim 13, wherein said first level shift circuit comprises:

first and second cross-coupled load P-channel MOS transistors whose sources receive said second positive voltage; and

first and second N-channel drive MOS transistors whose drains are connected to drains of said first and second cross-coupled load P-channel MOS transistors, respectively,

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No.: 10/684,441

gates of said first and second N-channel drive MOS transistors receiving said first clock signal and its inverted signal, respectively,

the drains of said first and second N-channel drive MOS transistors generating said second clock signals.

15. (Original) The step-up apparatus as set forth in claim 13, wherein said second level shift circuit comprises:

first and second cross-coupled N-channel load MOS transistors whose sources receive said voltage as said ground terminal; and

third and second P-channel drive MOS transistors whose sources receive said power supply voltage and whose drains are connected to drains of said first and second cross-coupled load N-channel MOS transistors, respectively,

gates of said first and second drive P-channel MOS transistors receiving said first clock signal and its inverted signal, respectively,

the drains of said first and second P-channel drive MOS transistors generating said third clock signals.

16. (Currently Amended) The step-up apparatus as set forth in claim 13, wherein said ~~change~~ charge pump circuit comprises:

a first circuit including a first step-up switching element, connected to said power supply voltage terminal, for generating said power supply voltage; and

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No.: 10/684,441

an i-th ( $i=2, 3, \dots, K$ ) circuit including a charging capacitor, a first charging ~~switching~~ element connected between said ground terminal and said charging capacitor, a second charging element connected between said charging capacitor and said power supply voltage terminal, and a second step-up switching element connected to said charging capacitor and said second charging ~~switching~~ element for generating an “i” times said power supply voltage,

said L-th ( $L=2, 3, \dots, K-1$ ) circuit generating said first positive voltage,

said K-th ( $K > L$ ) circuit generating said second positive voltage.

17. (Currently Amended) The step-up apparatus as set forth in claim 16, wherein each of said first and second step-up switching elements comprises a P-channel MOS transistor controlled by one of said second clock signals,

said first charging ~~switching~~ element comprising an N-channel MOS transistor controlled by the one of said second clock signals,

said second charging ~~switching~~ element comprising a P-channel MOS transistor controlled by the other of said second clock signals.

18. (Currently Amended) The step-up apparatus as set forth in claim 13, wherein said charge pump circuit steps up said power supply voltage further using said third clock signals, said charge pump circuit further comprising:

a first circuit including a first step-up switching element, connected to said power supply voltage terminal, for generating said power supply voltage; and

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No.: 10/684,441

an  $i$ -th ( $i=2, 3, \dots, K$ ) circuit including a charging capacitor, a first charging ~~switching~~ element connected between said ground terminal and said charging capacitor, a second charging element connected between said charging capacitor and said power supply voltage terminal, and a second step-up switching element connected to said charging capacitor and said second charging ~~switching~~ element for generating an " $i$ " times said power supply voltage,

said first step-up switching element comprising a P-channel MOS transistor controlled by one of said third clock signals,

said second charging ~~switching~~ element of said 2-nd circuit comprising a P-channel MOS transistor controlled by the other of said third clock signals,

said first charging ~~switching~~ element of said  $i$ -th ( $i=2, 3, \dots, K$ ) circuit comprising an N-channel MOS transistor controlled by the one of said second clock signals,

said second charging ~~switching~~ element of said  $i$ -th ( $i=3, 4, \dots, K$ ) circuit comprising a P-channel MOS transistor controlled by the other of said second clock signals,

said second step-up switching element comprising a P-channel MOS transistor controlled by the other of said second clock signal,

said  $L$ -th ( $L=2, 3, \dots, K-1$ ) circuit generating said first positive voltage,

said  $K$ -th ( $K > L$ ) circuit generating said second positive voltage.

19. (Original) A step-up apparatus comprising:

a first level shift circuit for receiving a clock first signal to generate two phase-opposite second clock signals;

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No.: 10/684,441

a second level shift circuit for receiving said first clock signal to generate a third clock signal;

a charge pump circuit, connected to said first level shift circuit, for stepping up a power supply voltage at a power supply voltage terminal using said second clock signals to generate first and second positive voltages; and

a polarity inverting circuit, connected to said charge pump circuit and said second level shift circuit, for inverting said second positive voltage using said third clock signal to generate a negative voltage whose absolute value is the same as said second positive voltage,

a high level of said second clock signals being not higher than said second positive voltage,

a low level of said second clock signals being not lower than a voltage at a ground terminal,

a high level of said third clock signal being not higher than said voltage at said ground voltage,

a low level of said third clock signal being not lower than said negative voltage.

20. (Original) The step-up apparatus as set forth in claim 19, wherein said first level shift circuit comprises:

first and second cross-coupled load P-channel MOS transistors whose sources receive said second positive voltage; and

first and second N-channel drive MOS transistors whose drains are connected to drains of said first and second cross-coupled load P-channel MOS transistors, respectively,

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No.: 10/684,441

gates of said first and second N-channel drive MOS transistors receiving said first clock signal and its inverted signal, respectively,

the drains of said first and second N-channel drive MOS transistors generating said second clock signals.

21. (Original) The step-up apparatus as set forth in claim 19, wherein said second level shift circuit comprises:

a polarity inverting circuit for inverting said first clock signal;

first and second cross-coupled N-channel Load MOS transistors whose sources receive said negative voltage; and

third and second P-channel drive MOS transistors whose sources receive said voltage at said ground terminal and whose drains are connected to drains of said first and second cross-coupled load N-channel MOS transistors, respectively,

gates of said first and second drive P-channel MOS transistors receiving an output signal of said polarity inverting circuit and its inverted signal, respectively,

the drain of one of said first and second P-channel drive MOS transistors generating said third clock signal.

22. (Original) The step-up apparatus as set forth in claim 21, wherein said polarity inverting circuit comprises a capacitor for receiving said first clock signal and a diode between said capacitor and said ground terminal.

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No.: 10/684,441

23. (Currently Amended) The step-up apparatus as set forth in claim 19, wherein said ~~change~~ charge pump circuit comprises:

a first circuit including a first step-up switching element, connected to said power supply voltage terminal, for generating said power supply voltage; and

an i-th ( $i=2, 3, \dots, K$ ) circuit including a charging capacitor, a first charging ~~switching~~ element connected between said ground terminal and said charging capacitor, a second charging element connected between said charging capacitor and said power supply voltage terminal, and a second step-up switching element connected to said charging capacitor and said second charging switching element for generating an "i" times said power supply voltage,

said L-th ( $L=2, 3, \dots$ ) circuit generating said first positive voltage,

said K-th ( $K > L$ ) circuit generating said second positive voltage,

24. (Currently Amended) The step-up apparatus as set forth in claim 23, wherein each of said first and second step-up switching elements comprises a P-channel MOS transistor controlled by one of said second clock signals,

said first charging ~~switching~~ element ~~comprising~~ comprises an N-channel MOS transistor controlled by the one of said second clock signals, and

said second charging ~~switching~~ element ~~comprising~~ comprises a P-channel MOS transistor controlled by the other of said second clock signals.

25. (Original) A step-up apparatus comprising:

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No.: 10/684,441

a first level shift circuit for receiving a clock first signal to generate two phase-opposite second clock signals;

a second level shift circuit for receiving said first clock signal to generate two phase-opposite third clock signals;

a charge pump circuit, connected to said first level shift circuit, for stepping up a power supply voltage at a power supply voltage terminal using said second clock signals to generate first and second positive voltages, said first positive voltage being smaller than said second positive voltage; and

a polarity inverting circuit, connected to said charge pump circuit and said second level shift circuit, for inverting said first positive voltage using said third clock signals to generate a negative voltage whose absolute value is the same as said first positive voltage,

a high level of said second clock signals being not higher than said first positive voltage,

a low level of said second clock signals being not lower than a voltage at a ground terminal,

a high level of said third clock signals being not higher than said power supply voltage,

a low level of said third clock signals being not lower than said negative voltage.

26. (Original) The step-up apparatus as set forth in claim 25, wherein said first level shift circuit comprises:

first and second cross-coupled load P-channel MOS transistors whose sources receive said first positive voltage; and

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No.: 10/684,441

first and second N-channel drive MOS transistors whose drains are connected to drains of said first and second cross-coupled load P-channel MOS transistors, respectively, gates of said first and second N-channel drive MOS transistors receiving said first clock signal and its inverted signal, respectively, the drains of said first and second N-channel drive MOS transistors generating said second clock signals.

27. (Original) The step-up apparatus as set forth in claim 25, wherein said second level shift circuit comprises:

first and second cross-coupled N-channel Load MOS transistors whose sources receive said voltage as said ground terminal; and

third and second P-channel drive MOS transistors whose sources receive said power supply voltage and whose drains are connected to drains of said first and second cross-coupled load N-channel MOS transistors, respectively,

gates of said first and second drive P-channel MOS transistors receiving said first clock signal and its inverted signal, respectively,

the drains of said first and second P-channel drive MOS transistors generating said third clock signals.

28. (Currently Amended) The step-up apparatus as set forth in claim 25, wherein said ~~change~~ charge pump circuit comprises:

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No.: 10/684,441

a first circuit including a first step-up switching element, connected to said power supply voltage terminal, for generating said power supply voltage; and

an i-th ( $i=2, 3, \dots, L$ ) circuit including a charging capacitor, a first charging ~~switching~~ element connected between said ground terminal and said charging capacitor, a second charging element connected between said charging capacitor and said power supply voltage terminal, and a second step-up switching element connected to said charging capacitor and said second charging ~~switching~~ element for generating an “i” times said power supply voltage,

said ~~a~~ K-th ( $K=2, 3, \dots, L-1$ ) circuit generating said first positive voltage, and

said an L-th ( $L > K$ ) circuit generating said second positive voltage.

29. (Currently Amended) The step-up apparatus as set forth in claim 28, wherein each of said first and second step-up switching elements comprises a P-channel MOS transistor controlled by one of said second clock signals,

said first charging ~~switching~~ element comprising an N-channel MOS transistor controlled by the one of said second clock signals,

said second charging ~~switching~~ element comprising a P-channel MOS transistor controlled by the other of said second clock signals.

30. (Currently Amended) The step-up apparatus as set forth in claim 25, wherein said charge pump circuit steps up said power supply voltage further using said third clock signals, said pump circuit comprising:

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No.: 10/684,441

a first circuit including a first step-up switching element, connected to said power supply voltage terminal, for generating said power supply voltage; and

an i-th ( $i=2, 3, \dots, L$ ) circuit including a charging capacitor, a first charging ~~switching~~ element connected between said ground terminal and said charging capacitor, a second charging element connected between said charging capacitor and said power supply voltage terminal, and a second step-up switching element connected to said charging capacitor and said second charging ~~switching~~ element for generating an “i” times said power supply voltage,

said first step-up switching element comprising a P-channel MOS transistor controlled by one of said third clock signals,

said second charging ~~switching~~ element of said 2-nd circuit comprising a P-channel MOS transistor controlled by the other of said third clock signals,

said first charging ~~switching~~ element of said i-th ( $i=2, 3, \dots, L$ ) circuit comprising an N-channel MOS transistor controlled by the one of said second clock signals,

said second charging ~~switching~~ element of said i-th ( $i=3, 4, \dots, L$ ) circuit comprising a P-channel MOS transistor controlled by the other of said second clock signals,

said second step-up switching element comprising a P-channel MOS transistor controlled by the other of said second clock signal,

~~said a~~ K-th ( $K=2, 3, \dots, L-1$ ) circuit generating said first positive voltage, and

~~said an~~ L-th ( $L > K$ ) circuit generating said second positive voltage.

31. (Original) A step-up apparatus comprising:

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No.: 10/684,441

a first level shift circuit for receiving a clock first signal to generate two phase-opposite second clock signals;

a second level shift circuit for receiving said first clock signal to generate a third clock signal;

a charge pump circuit, connected to said first level shift circuit, for stepping up a power supply voltage at a power supply voltage terminal using said second clock signals to generate first and second positive voltages; and

a polarity inverting circuit, connected to said charge pump circuit and said second level shift circuit, for inverting said first positive voltage using said third clock signal to generate a negative voltage whose absolute value is the same as said first positive voltage,

a high level of said second clock signals being not higher than said first positive voltage,

a low level of said second clock signals being not lower than a voltage at a ground terminal,

a high level of said third clock signal being not higher than said voltage at said ground voltage,

a low level of said third clock signal being not lower than said negative voltage.

32. (Original) The step-up apparatus as set forth in claim 31, wherein said first level shift circuit comprises:

first and second cross-coupled load P-channel MOS transistors whose sources receive said first positive voltage; and

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No.: 10/684,441

first and second N-channel drive MOS transistors whose drains are connected to drains of said first and second cross-coupled load P-channel MOS transistors, respectively, gates of said first and second N-channel drive MOS transistors receiving said first clock signal and its inverted signal, respectively, the drains of said first and second N-channel drive MOS transistors generating said second clock signals.

33. (Original) The step-up apparatus as set forth in claim 31, wherein said second level shift circuit comprises:

a polarity inverting circuit for inverting said first clock signal; first and second cross-coupled N-channel Load MOS transistors whose sources receive said negative voltage; and third and second P-channel drive MOS transistors whose sources receive said voltage at said ground terminal and whose drains are connected to drains of said first and second cross-coupled load N-channel MOS transistors, respectively, gates of said first and second drive P-channel MOS transistors receiving an output signal of said polarity inverting circuit and its inverted signal, respectively, the drain of one of said first and second P-channel drive MOS transistors generating said third clock signal.

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No.: 10/684,441

34. (Original) The step-up apparatus as set forth in claim 33, wherein said polarity inverting circuit comprises a capacitor for receiving said first clock signal and a diode between said capacitor and said ground terminal.

35. (Currently Amended) The step-up apparatus as set forth in claim 31, wherein said ~~ehange~~ charge pump circuit comprises:

a first circuit including a first step-up switching element, connected to said power supply voltage terminal, for generating said power supply voltage; and

an i-th ( $i=2, 3, \dots, L$ ) circuit including a charging capacitor, a first charging ~~switching~~ element connected between said ground terminal and said charging capacitor, a second charging element connected between said charging capacitor and said power supply voltage terminal, and a second step-up switching element connected to said charging capacitor and said second charging ~~switching~~ element for generating an “i” times said power supply voltage,

~~said a~~ K-th ( $K=2, 3, \dots$ ) circuit generating said first positive voltage, and

~~said an~~ L-th ( $L > K$ ) circuit generating said second positive voltage,

36. (Currently Amended) The step-up apparatus as set forth in claim 35, wherein each of said first and second step-up switching elements comprises a P-channel MOS transistor controlled by one of said second clock signals,

said first charging ~~switching~~ element comprising an N-channel MOS transistor controlled by the one of said second clock signals,

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No.: 10/684,441

said second charging ~~switching~~ element comprising a P-channel MOS transistor controlled by the other of said second clock signals.

37. (Currently Amended) A step-up apparatus comprising:

a first level shift circuit for receiving a first clock signal to generate a 2nd clock signal, a 3rd clock signal, ..., a K-th clock signal ( $K = 2, 3, \dots$ ) having a definite voltage swing;

a second level shift circuit for receiving said first clock signal to generate two phase-opposite third clock signals;

a charge pump circuit, connected to said first level shift circuit, for stepping up a power supply voltage at a power supply voltage terminal using said first, second, ..., K-th clock signals to generate a positive voltage; and

a polarity inverting circuit, connected to said charge pump circuit and said second level shift circuit, for inverting said positive voltage using said third clock signals to generate a negative voltage whose absolute value is the same as said positive voltage[[],].

38. (Currently Amended) The step-up apparatus as set forth in claim 37, wherein said ~~change~~ charge pump circuit comprises:

a first circuit including a first step-up switching element, connected to said power supply voltage terminal, for generating said power supply voltage in accordance with said first clock signal;

an i-th ( $i = 2, 3, \dots, K$ ) circuit including a charging capacitor, a first charging ~~switching~~ element connected between said ground terminal and said charging capacitor, a second charging

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No.: 10/684,441

element connected between said charging capacitor and said power supply voltage terminal, and  
a second step-up switching element connected to said charging capacitor and said second  
charging ~~switching~~ element for generating an “i” times said power supply voltage.

39. (Currently Amended) The step-up apparatus as set forth in claim 38, wherein said first  
step-up switching element comprises a P-channel MOS transistor controlled by said first clock  
signal,

said first charging ~~switching~~ element comprising an N-channel MOS transistor  
controlled by said first clock signal,

said second charging ~~switching~~ element comprising an N-channel MOS transistor  
controlled by said second clock signal,

said second step-up switching element of said i-th ( $i = 2, 3, \dots, K$ ) circuit comprising a  
P-channel MOS transistor controlled by said i-th clock signal.

40. (Original) The step-up apparatus as set forth in claim 38, wherein said first level shift  
circuit comprises an i-th ( $i = 2, 3, \dots, K$ ) level shift unit is powered by  $(i-2) \cdot V_{DD}$ ,  $(i-1) \cdot V_{DD}$  and  
 $i \cdot V_{DD}$  where  $V_{DD}$  is a power supply voltage.

41. (Original) The step-up apparatus as set forth in claim 40, wherein said i-th level shift  
unit comprises:

cross-coupled first and second load N-channel MOS transistors whose sources receive  
 $(i-2) \cdot V_{DD}$ ;

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No.: 10/684,441

first and second drive P-channel MOS transistors whose sources receive  $(i-1) \cdot V_{DD}$  and whose drains are connected to drains of said first and second load N-channel MOS transistors, respectively;

cross-coupled first and second load P-channel MOS transistors whose sources receive  $i \cdot V_{DD}$ ; and

first and second drive N-channel MOS transistors whose sources receive  $(i-2) \cdot V_{DD}$ , whose drains are connected to drains of said first and second load P-channel MOS transistors, respectively, and whose gates are connected to gates of said first and second load N-channel MOS transistors, respectively,

gates of said first and drive P-channel MOS transistors receiving said  $(i-1)$ -th clock signal and its inverted signal,

the drain of said second drive N-channel MOS transistor generating said  $i$ -th clock signal via an inverter.

42. (Currently Amended) A step-up apparatus comprising:

a level shift circuit for receiving a first clock signal to generate a 2nd clock signal, a 3rd clock signal, ..., a  $K$ -th clock signal ( $K = 2, 3, \dots$ ) having a definite voltage swing; and

a charge pump circuit, connected to said a first level shift circuit, for stepping up a power supply voltage at a power supply voltage terminal using said first, second, ...,  $K$ -th clock signals to generate a positive voltage, said charge pump comprising:

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No.: 10/684,441

a first circuit including a first step-up switching element, connected to said power supply voltage terminal, for generating said power supply voltage in accordance with said first clock signal;

an i-th (i=2, 3, ..., K) circuit including a charging capacitor, a first charging element connected between a ground terminal and said charging capacitor, a second charging element connected between said charging capacitor and said power supply voltage terminal, and a second step-up switching element connected to said charging capacitor and said second charging element for generating an "i" times said power supply voltage; wherein

said second step-up switching element of said i-th (i= 2, 3, ..., K) circuit comprises a P-channel MOS transistor controlled by an i-th clock signal.

43. (Cancelled).

44. (Currently Amended) The step-up apparatus as set forth in claim ~~[[43]]~~ 42, wherein:

said first step-up switching element comprises a P-channel MOS transistor controlled by said first clock signal,

said first charging ~~switching~~ element comprising an N-channel MOS transistor controlled by said first clock signal, and

said second charging ~~switching~~ element comprising an N-channel MOS transistor controlled by said second clock signal;

~~said second step-up switching element of said i-th (i= 2, 3, ..., K) circuit comprising a P-channel MOS transistor controlled by said i-th clock signal.~~

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No.: 10/684,441

45. (Currently Amended) The step-up apparatus as set forth in claim ~~[[43]]~~ 42, wherein said level shift circuit comprises an i-th ( $i = 2, 3, \dots, K$ ) level shift unit is powered by  $(i-2) \cdot V_{DD}$ ,  $(i-1) \cdot V_{DD}$  and  $i \cdot V_{DD}$  where  $V_{DD}$  is a power supply voltage.

46. (Currently Amended) The step-up apparatus as set forth in claim 45, wherein said i-th level shift unit comprises:

cross-coupled first and second load N-channel MOS transistors whose sources receive  $(i-2) \cdot V_{DD}$ ;

first and second drive P-channel MOS transistors whose sources receive  $(i-1) \cdot V_{DD}$  and whose drains are connected to drains of said first and second load N-channel MOS transistors, respectively;

cross-coupled first and second load P-channel MOS transistors whose sources receive  $i \cdot V_{DD}$ ; and

first and second drive N-channel MOS transistors whose sources receive  $(i-2) \cdot V_{DD}$ , whose drains are connected to drains of said first and second load P-channel MOS transistors, respectively, and whose gates are connected to gates of said first and second load N-channel MOS transistors, respectively,

gates of said first and drive P-channel MOS transistors receiving said ~~an~~ an (i-1)-th clock signal and its inverted signal,

the drain of said second drive N-channel MOS transistor generating said i-th clock signal via an inverter.

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No.: 10/684,441

47. (New) A step-up apparatus comprising:

a level shift circuit for receiving a first clock signal to generate a 2nd clock signal, a 3rd clock signal, ..., a K-th clock signal ( $K = 2, 3, \dots$ ) having a definite voltage swing; and a charge pump circuit, connected to a first level shift circuit, for stepping up a power supply voltage at a power supply voltage terminal using said first, second, ..., K-th clock signals to generate a positive voltage, wherein said level shift circuit comprises an i-th ( $i = 2, 3, \dots, K$ ) level shift unit that is powered by  $(i-2) \cdot V_{DD}$ ,  $(i-1) \cdot V_{DD}$  and  $i \cdot V_{DD}$  where  $V_{DD}$  is a power supply voltage.